

## HWGH Series Gas Generator Sets Powered by Howin H series Engines



### HWGH206-G 50HZ

#### Ratings

Rated Power	kVA	187.5
	kW	150
Standby Power	kVA	206
	kW	165
Voltage type		50Hz,380/220V, 3 phases and 4 wires

Ratings at 0.8 power factor

#### Performance Data

Engine Brand & Model	HGNT14
Alternator Brand & Model	LSA46.2M5/160KW
Control System	Deepsea DSE7320
Standard Noise Level@7m (Soundproof Sets)	75 dBA
Circuit Breaker Type	3 Poles MCCB
Frequency & Phase	50hz 3Phases + 4Wires
Engine Speed (RPM)	1500
Fuel Consumption (Nm <sup>3</sup> /hr) 100% Load	48.66

The above fuel consumption is calculate with the natural gas whose heat value is 35.8MJ/Nm<sup>3</sup>

#### Dimensions and Weights

Content		Open type	Soundproof Sets
Dimensions: (mm)	L	3150	4350
	W	1100	1450
	H	1800	1900
Weights (kg)		2525	4365

## Engine Brand & Model: HGNT14

### Engine Data

No. of Cylinders	6 in-line	Engine power(KW)	240
Cycle	4 Stroke	Cylinder Type	Wet
Bore * Stroke (mm)	140 * 152	Compression Ratio	11:1
Induction	Turbocharged& Aftercooled	Displacement (L)	14
Cooling Method	Water cooled	Governing Type	Electronic
Starting method	24V DC motor	Coolant capacity, including radiator (L)	66.8
Lubricant Oil	15W40-CF4 or above grade	Oil pan capacity (L)	36

## Alternator Brand & Model: LSA46.2M5, 50Hz.

### Standard Leroy Somer Alternator Data

Continuous power	200kVA/160kW	Efficiency (%)	92.3
Power factor	0.8	Temperature rise	125K
Excitation system	Brushless, self-excited	Insulation class	H
A.V.R.	R250	Enclosure protection	IP23
Voltage regulation	± 0.5 %	Winding leads	12
Altitude	≤ 1000 m	Ambient temperature (°C)	40

## Controller Brand & Model: Deepsea DSE7320



The DSE7320 is an Auto Start & Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications. It monitors speed, frequency, voltage, current, oil pressure, coolant temperature and fuel level, and the modules will display warnings, shutdown and engine status information on the back-lit LCD screen and illuminated LED.

The controller offers electronic (CAN) and non-electronic (magnetic pick-up/alternator sensing) engine versions and offer a number of flexible inputs, outputs and engine protections so the system can be easily adapted to suit a wide range of application demands.

The controller can also be easily configured using the DSE Configuration Suite PC software. Selected front panel editing is also available.

## Optional Configuration

Engine	Alternator	Control System	Canopy	Voltages
<ul style="list-style-type: none"><li>● Jacket Water Preheater</li><li>● Oil Preheater</li><li>● Automatic Oil filling system</li><li>● Cogeneration</li><li>● Remote cooling radiator</li></ul>	<ul style="list-style-type: none"><li>● Winding Temperature</li><li>● Measuring Instrument</li><li>● Alternator Space Heater</li><li>● PMG</li><li>● Marine grade Protection (anti-corrosion)</li></ul>	<ul style="list-style-type: none"><li>● Remote control panel</li><li>● ATS</li><li>● Synchronizing to grid cabinet</li><li>● Paralleling cabinet</li></ul>	<ul style="list-style-type: none"><li>● Trailer</li><li>● Galvanized powder coating</li><li>● Containerized canopy</li></ul>	<ul style="list-style-type: none"><li>● 440/254V</li><li>● 380/220V</li><li>● 220/127V</li><li>● 208/120V</li></ul>

## Following spare parts list is optional according to customer requirements.

- FILTER, LUBRICATION
- FILTER, AIR
- BELT, ALTERNATOR
- BELT, FAN
- SPARK PLUG



E-Mail: [sales@howinpower.com](mailto:sales@howinpower.com)  
Website: [www.howinpower.com](http://www.howinpower.com)

We reserve the right to change above information about model, technical specification, color, configuration and accessories without prior notice. Please contact with us before confirmation.

**Distributed by**